Infinium MethylationEPIC BeadChip Kit (Illumina) Acute Leukemia of Ambiguous Lineage (ALAL) – Methylation

*Protocol performed at St. Jude Children's Research Hospital.

Raw data from the Infinium MethylationEPIC BeadChip Kit (Illumina Inc.) were analyzed using the ChAMP¹ R package.

In general, the raw *.idat files were imported through "minfi" method² and then the following filters were applied to exclude the probes: 1) with detection P-value above 0.01 in one or more samples; 2) with beadcount <3 in at least 5% of samples; 3) as non-CpG probes, 4) identified as SNPs³; 5) aligned to multiple locations⁴ and 6) on the X or Y chromosome. After filtering, "BMIQ" normalization from ChAMP package was used as the author suggested to calculate methylation beta values. Batch effect was observed by the singular value decomposition method⁵ and adjusted by ComBat normalization method⁶.

References

- 1. Morris TJ, et al. (2014). ChAMP: 450k Chip Analysis Methylation Pipeline. Bioinformatics. 30(3):428-30. (PMID: 24336642)
- 2. Aryee MJ, et al. (2014). Minfi: a flexible and comprehensive Bioconductor package for the analysis of Infinium DNA methylation microarrays. Bioinformatics. 30(10):1363-9. (PMID: 24478339)
- 3. Zhou W, et al. (2017). Comprehensive characterization, annotation and innovative use of Infinium DNA methylation BeadChip probes. Nucleic Acids Res. 45(4):e22. (PMID: 27924034)
- 4. Nordlund J, et al. (2013). Genome-wide signatures of differential DNA methylation in pediatric acute lymphoblastic leukemia. Genome Biol. 14(9):r105. (PMID: 24063430)
- 5. Teschendorff AE, et al. (2009). An epigenetic signature in peripheral blood predicts active ovarian cancer. PloS One. 4(12):e8274. (PMID: 20019873)
- 6. Johnson WE, et al. (2007). Adjusting batch effects in microarray expression data using empirical Bayes methods. Biostatistics. 8(1):118-27. (PMID: 16632515)